

EN

EN

EN



COMMISSION OF THE EUROPEAN COMMUNITIES

Brussels,
C(2008)

Draft

COMMISSION DECISION

of [...]

**amending Decision 2006/771/EC on harmonisation of the radio spectrum for use by
short-range devices**

Draft

COMMISSION DECISION

of [...]

amending Decision 2006/771/EC on harmonisation of the radio spectrum for use by short-range devices

(Text with EEA relevance)

THE COMMISSION OF THE EUROPEAN COMMUNITIES,

Having regard to the Treaty establishing the European Community,

Having regard to Decision No 676/2002/EC of the European Parliament and of the Council of 7 March 2002 on a regulatory framework for radio spectrum policy in the European Community (Radio Spectrum Decision)¹, and in particular Article 4(3) thereof,

Whereas:

- (1) Commission Decision 2006/771/EC harmonises the technical conditions for use of spectrum for a wide variety of short-range devices, including applications such as alarms, local communications equipment, door openers and medical implants. Short-range devices are typically mass-market and/or portable products which can easily be taken and used across borders; differences in spectrum access conditions therefore prevent their free movement, increase their production costs and create risks of harmful interference with other radio applications and services.
- (2) Commission Decision 2008/432/EC² amended the harmonised technical conditions for short-range devices contained in Decision 2006/771/EC³ by replacing its Annex.
- (3) However, due to rapid changes in technology and societal demands, new applications for short-range devices can emerge which require regular updates of spectrum harmonisation conditions.
- (4) On 5 July 2006, the Commission issued a permanent mandate⁴ to the European Conference of Postal and Telecommunications Administrations (CEPT), pursuant to Article 4(2) of Decision No 676/2002/EC, to update the Annex to Decision 2006/771/EC in response to the technological and market developments in the area of short-range devices.

¹ OJ L 108, 24.4.2002, p. 1.

² OJ L 151, 11.6.2008, p. 49.

³ OJ L 312, 11.11.2006, p. 66.

⁴ Permanent Mandate to CEPT regarding the annual update of the technical annex of the Commission Decision on the technical harmonisation of radio spectrum for use by Short Range Devices. (5 July 2006).

- (5) In its November 2008 report⁵ submitted in response to that mandate, the CEPT advised the Commission to amend a number of technical aspects in the Annex to Decision 2006/771/EC.
- (6) Decision 2006/771/EC should therefore be amended accordingly.
- (7) Equipment operating within the conditions set in this Decision must also comply with Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity⁶ in order to use the spectrum effectively so as to avoid harmful interference, demonstrated either by meeting harmonised standards or by fulfilling alternative conformity assessment procedures.
- (8) The measures provided for in this Decision are in accordance with the opinion of the Radio Spectrum Committee,

HAS ADOPTED THIS DECISION:

Article 1

The Annex to Decision 2006/771/EC is replaced by the Annex to this Decision.

Article 2

This Decision is addressed to the Member States.

Done at Brussels, [...]

For the Commission

[...]

Member of the Commission

⁵ CEPT Report 26, RSCOM 08-88.

⁶ OJ L 91, 7.4.1999, p. 10.

ANNEX

Harmonised frequency bands and technical parameters for short-range devices

Type of short-range device	Frequency band	Power limit / field strength limit / power density limit ⁷	Additional parameters / spectrum access and mitigation requirements ⁸	Other usage restrictions ⁹	Implementation deadline
Non-specific short-range devices ¹⁰	6765 - 6795 kHz	42 dB μ A/m at 10 metres			1 October 2008
	13,553 - 13,567 MHz	42 dB μ A/m at 10 metres			1 October 2008
	26,957 - 27,283 MHz	10 mW effective radiated power (e.r.p.), which corresponds to 42 dB μ A/m at 10 metres		Video applications are excluded	1 June 2007
	40,660 - 40,700 MHz	10 mW e.r.p.		Video applications are excluded	1 June 2007

⁷ Member States must allow the usage of spectrum up to the power, field strength or power density given in this table. In conformity with Article 3(3) of Decision 2006/771/EC, they may impose less restrictive conditions, i.e. allow the use of spectrum with higher power, field strength or power density.

⁸ Member States may only impose these 'additional parameters / spectrum access and mitigation requirements', and may not add other parameters or spectrum access and mitigation requirements. Less restrictive conditions within the meaning of Article 3(3) of Decision 2006/771/EC mean that Member States may completely omit the parameters / spectrum access and mitigation requirements in a given cell or allow higher values.

⁹ Member States may only impose these 'other usage restrictions', and may not add additional usage restrictions. As less restrictive conditions may be introduced within the meaning of Article 3(3) of Decision 2006/771/EC, Member States may omit one or all of these restrictions.

¹⁰ This category is available for any type of application which fulfils the technical conditions (typical uses are telemetry, telecommand, alarms, data in general and other similar applications).

Non-specific short-range devices (cont.)	433,050 - 434,040 ¹¹ MHz	1 mW e.r.p. and -13dBm/10 kHz power density for bandwidth modulation larger than 250 kHz		Audio and voice signals, and video applications, are excluded	1 October 2008
		10 mW e.r.p.	Duty cycle ¹² : 10%	Audio and voice signals, and video applications, are excluded	1 June 2007
	434,040 - 434,790 ¹¹ MHz	1 mW e.r.p. and -13dBm/10 kHz power density for bandwidth modulation larger than 250 kHz		Audio and voice signals, and video applications, are excluded	1 October 2008
		10 mW e.r.p.	Duty cycle ¹² : 10%	Audio and voice signals, and video applications, are excluded	1 June 2007
			Duty cycle ¹² : 100% subject to channel spacing up to 25 kHz	Audio and voice signals, and video applications, are excluded	1 October 2008

¹¹ For this frequency band Member States must make all the alternative sets of usage conditions possible.

¹² 'Duty cycle' means the ratio of time during any one-hour period when equipment is actively transmitting. Less restrictive conditions within the meaning of Article 3(3) of Decision 2006/771/EC mean that Member States may allow a higher value for 'Duty cycle'.

Non-specific short-range devices (cont.)	863,000 - 868,000 MHz	25 mW e.r.p.	Techniques to access spectrum and mitigate interference that provide at least equivalent performance to the techniques described in harmonised standards adopted under Directive 1999/5/EC must be used. Alternatively a duty cycle ¹² of 0,1% may also be used	Audio and voice signals, and video applications, are excluded	1 October 2008
	868,000 - 868,600 ¹¹ MHz	25 mW e.r.p.	Techniques to access spectrum and mitigate interference that provide at least equivalent performance to the techniques described in harmonised standards adopted under Directive 1999/5/EC must be used. Alternatively a duty cycle ¹² of 1% may also be used	Video applications are excluded	1 October 2008
		25 mW e.r.p.	Techniques to access spectrum and mitigate interference that provide at least equivalent performance to the techniques described in harmonised standards adopted under Directive 1999/5/EC must be used. Alternatively a duty cycle ¹² of 0,1% may also be used	Audio and voice signals, and video applications, are excluded	1 October 2008

Non-specific short-range devices (cont.)	868,700 - 869,200 ¹¹ MHz	25 mW e.r.p.	Techniques to access spectrum and mitigate interference that provide at least equivalent performance to the techniques described in harmonised standards adopted under Directive 1999/5/EC must be used. Alternatively a duty cycle ¹² of 0,1% may also be used	Video applications are excluded	1 October 2008
		25 mW e.r.p.	Techniques to access spectrum and mitigate interference that provide at least equivalent performance to the techniques described in harmonised standards adopted under Directive 1999/5/EC must be used. Alternatively a duty cycle ¹² of 0,1% may also be used	Audio and voice signals, and video applications, are excluded	1 October 2008

Non-specific short-range devices (cont.)	869,400 - 869,650 ¹¹ MHz	500 mW e.r.p.	Techniques to access spectrum and mitigate interference that provide at least equivalent performance to the techniques described in harmonised standards adopted under Directive 1999/5/EC must be used. Alternatively a duty cycle ¹² of 10 % may also be used Channel spacing must be 25 kHz, except that the whole band may also be used as a single channel for high-speed data transmission	Video applications are excluded	1 October 2008
		25 mW e.r.p.	Techniques to access spectrum and mitigate interference that provide at least equivalent performance to the techniques described in harmonised standards adopted under Directive 1999/5/EC must be used. Alternatively a duty cycle ¹² of 0,1% may also be used	Audio and voice signals, and video applications, are excluded	1 October 2008
	869,700 - 870,000 ¹¹ MHz	5 mW e.r.p.	Voice applications allowed with advanced mitigation techniques	Audio and video applications are excluded	1 June 2007
		25 mW e.r.p.	Techniques to access spectrum and mitigate interference that provide at least equivalent performance to the techniques described in harmonised standards adopted under Directive 1999/5/EC must be used. Alternatively a duty cycle ¹² of 0,1% may also be used	Audio and voice signals, and video applications, are excluded	1 October 2008

Non-specific short-range devices (cont.)	2400 - 2483,5 MHz	10 mW equivalent isotropic radiated power (e.i.r.p.)			1 June 2007
	5725 - 5875 MHz	25 mW e.i.r.p.			1 June 2007
	24,150 - 24,250 GHz	100 mW e.i.r.p.			1 October 2008
	61,0 - 61,5 GHz	100 mW e.i.r.p.			1 October 2008
Wideband data transmission systems	2400 - 2483,5 MHz	100 mW e.i.r.p. and 100 mW/100 kHz e.i.r.p. density applies when frequency hopping modulation is used, 10 mW/MHz e.i.r.p. density applies when other types of modulation are used	Techniques to access spectrum and mitigate interference that provide at least equivalent performance to the techniques described in harmonised standards adopted under Directive 1999/5/EC must be used.		1 November 2009
	57,0 – 66,0 ¹¹ GHz	40 dBm e.i.r.p. and 13 dBm/MHz e.i.r.p. density		Outdoor applications are excluded	1 November 2009
		25 dBm e.i.r.p. and -2 dBm/MHz e.i.r.p. density		Fixed outdoor installations are excluded	1 November 2009

Alarm systems	868,600 - 868,700 MHz	10 mW e.r.p.	Channel spacing: 25 kHz The whole frequency band may also be used as a single channel for high-speed data transmission Duty cycle ¹² : 1.0%		1 October 2008
	869,250 - 869,300 MHz	10 mW e.r.p.	Channel spacing: 25 kHz Duty cycle ¹² : 0.1%		1 June 2007
	869,300 – 869,400 MHz	10 mW e.r.p.	Channel spacing: 25 kHz Duty cycle ¹² : 1.0%		1 October 2008
	869,650 - 869,700 MHz	25 mW e.r.p.	Channel spacing: 25 kHz Duty cycle ¹² : 10%		1 June 2007
Social alarms ¹³	869,200 – 869,250 MHz	10 mW e.r.p.	Channel spacing: 25 kHz Duty cycle ¹² : 0.1%		1 June 2007

¹³ Social alarm devices are used to assist elderly or disabled people when they are in distress.

Inductive applications ¹⁴	20,050 - 59,750 kHz	72 dB μ A/m at 10 metres			1 June 2007
	59,750 - 60,250 kHz	42 dB μ A/m at 10 metres			1 June 2007
	60,250 - 70,000 kHz	69 dB μ A/m at 10 metres			1 June 2007
	70 - 119 kHz	42 dB μ A/m at 10 metres			1 June 2007
	119 - 127 kHz	66 dB μ A/m at 10 metres			1 June 2007
	127 - 140 kHz	42 dB μ A/m at 10 metres			1 October 2008
	140 - 148,5 kHz	37,7 dB μ A/m at 10 metres			1 October 2008
	148,5 - 5000 kHz In the specific bands mentioned below, higher field strengths and additional usage restrictions apply:	-15 dB μ A/m at 10 metres in any bandwidth of 10 kHz Furthermore the total field strength is -5 dB μ A/m at 10 m for systems operating at bandwidths larger than 10 kHz			1 October 2008

¹⁴ This category covers, for example, devices for car immobilisation, animal identification, alarm systems, cable detection, waste management, personal identification, wireless voice links, access control, proximity sensors, anti-theft systems, including RF anti-theft induction systems, data transfer to handheld devices, automatic article identification, wireless control systems and automatic road tolling.

Inductive applications (cont.)	400 - 600 kHz	-8 dB μ A/m at 10 metres		This set of usage conditions applies to RFID ¹⁵ only	1 October 2008
	3155 - 3400 kHz	13,5 dB μ A/m at 10 metres			1 October 2008
	5000 - 30000 kHz In the specific bands mentioned below, higher field strengths and additional usage restrictions apply:	-20 dB μ A/m at 10 metres in any bandwidth of 10 kHz Furthermore the total field strength is -5 dB μ A/m at 10 m for systems operating at bandwidths larger than 10 kHz			1 October 2008
	6765 - 6795 kHz	42 dB μ A/m at 10 metres			1 June 2007
	7400 - 8800 kHz	9 dB μ A/m at 10 metres			1 October 2008
	10200 - 11000 kHz	9 dB μ A/m at 10 metres			1 October 2008

¹⁵ This category covers inductive applications used for Radio Frequency Identification (RFID).

Inductive applications (cont.)	13553 - 13567 kHz	42 dB μ A/m at 10 metres			1 June 2007
		60 dB μ A/m at 10 metres		This set of usage conditions applies to RFID ¹⁵ and EAS ¹⁶ only	1 October 2008
	26957 - 27283 kHz	42 dB μ A/m at 10 metres			1 October 2008
Active medical implants ¹⁷	9 - 315 kHz	30 dB μ A/m at 10m	Duty cycle ¹² : 10%		1 October 2008
	402 - 405 MHz	25 μ W e.r.p.	Channel spacing: 25 kHz Individual transmitters may combine adjacent channels for increased bandwidth up to 300 kHz. Other techniques to access spectrum or mitigate interference, including bandwidths greater than 300 kHz, can be used provided they result at least in an equivalent performance to the techniques described in harmonised standards adopted under Directive 1999/5/EC to ensure compatible operation with the other users and in particular with meteorological radiosondes.		1 November 2009

¹⁶ This category covers inductive applications used for Electronic Article Surveillance (EAS).

¹⁷ This category covers the radio part of active implantable medical devices, as defined in Council Directive 90/385/EEC of 20 June 1990 on the approximation of the laws of the Member States relating to active implantable medical devices and their peripherals (OJ L 189, 20.7.1990, p. 17).

Wireless audio applications ¹⁸	87,5 - 108,0 MHz	50 nW e.i.r.p.	Channel spacing up to 200 kHz		1 October 2008
	863 - 865 MHz	10 mW e.i.r.p.			1 June 2007
Radio determination applications ¹⁹	2400 - 2483,5 MHz	25 mW e.i.r.p.			1 November 2009
	17,1 – 17,3 GHz	26 dBm e.i.r.p.	Techniques to access spectrum and mitigate interference that provide at least equivalent performance to the techniques described in harmonised standards adopted under Directive 1999/5/EC must be used.	This set of usage conditions applies to ground based systems only	1 November 2009
Tank Level Probing Radar ²⁰	4,5 - 7,0 GHz	24 dBm e.i.r.p. ²¹			1 November 2009
	8,5 - 10,6 GHz	30 dBm e.i.r.p. ²¹			1 November 2009
	24,05 - 27,0 GHz	43 dBm e.i.r.p. ²¹			1 November 2009
	57,0 - 64,0 GHz	43 dBm e.i.r.p. ²¹			1 November 2009
	75,0 – 85,0 GHz	43 dBm e.i.r.p. ²¹			1 November 2009

¹⁸ Applications for wireless audio systems, including: cordless loudspeakers; cordless headphones; cordless headphones for portable use, e.g. portable CD, cassette or radio devices carried on a person; cordless headphones for use in a vehicle, for example for use with a radio or mobile telephone, etc.; in-ear monitoring, for use at concerts or other stage productions.

¹⁹ This category covers applications used for determining the position, velocity and/or other characteristics of an object, or for obtaining information relating to these parameters.

²⁰ Tank Level Probing Radars (TLPR) are a specific type of radiodetermination application, which are used for tank level measurements and are installed in metallic or reinforced concrete tanks, or similar structures made of material with comparable attenuation characteristics. The purpose of the tank is to contain a substance.

²¹ The power limit applies inside a closed tank and corresponds with a spectral density of -41,3 dBm/MHz e.i.r.p. outside a 500 litre test tank.

Model Control ²²	26990 - 27000 kHz	100 mW e.r.p.			1 November 2009
	27040 - 27050 kHz	100 mW e.r.p.			1 November 2009
	27090 - 27100 kHz	100 mW e.r.p.			1 November 2009
	27140 - 27150 kHz	100 mW e.r.p.			1 November 2009
	27190 - 27200 kHz	100 mW e.r.p.			1 November 2009
Radio Frequency Identification (RFID)	2446 - 2454 MHz	100 mW e.i.r.p.			1 November 2009

²² This category covers applications used to control the movement of models (principally miniature representations of vehicles) in the air, on land or over or under the water surface.